


Additional Features:

- » High-pressure injection molded using a proprietary material blend, specifically formulated to deliver superior performance and extended product life
- » Two-piece welded design with enhanced internal deck ribbing delivers strength and durability with low tare weight, offering superior handling of heavier loads
- » Patent pending *Flex Foot* design absorbs impact, resists breakage and damage to key impact crash zones
- » Ergonomic handles enable gripping from any side and can be used to de-nest pallet even when flush with another pallet below. Handle placement facilitates safer handling and helps prevent operator injury
- » Space-saving nestable design improves efficiency, minimizing space needed for storage and maximizing backhaul quantities when empty
- » Designated locations for optional engraving, hotstamps, barcodes, or labels for identification and tracking


Specifications:

Model	Entry	Material	Outside Dimensions (inches)			Pallet Weight (lbs)	Static Load (lbs)	Dynamic Load (lbs)	Stack Qty	Trailer Qty 53'
			L	W	H					
NP 4840-6-IM-W G2	4-Way	PE	48.0	40.0	6.5	25.0	10,000	3,000	42	1,260

Static and Dynamic Load ratings are affected by type and distribution of load. Contact your Monoflo Sales Rep to discuss your application.



48" side view



40" side view



Monoflo International
882 Baker Lane, Winchester, VA 22603
Call 540-771-3077

miworldwide.com



defining what comes next.