

Stronger corner design means increased durability which translates to fewer damaged containers.

DC 2515-14



Secure plastic hinges make containers safer to handle and easier to recycle at end-of-life.

Enhanced nesting lug increases strength when stacking.

**Distribution Container Specifications:**

| Model         | Outside Dimensions (inches) |      |        |      | Inside Dimensions (inches) |      |        |      | Total Container Height (inches) | Product Clearance (inches) | Weight (lbs) | Volume (cubic feet) | Trailer Qty 53' |
|---------------|-----------------------------|------|--------|------|----------------------------|------|--------|------|---------------------------------|----------------------------|--------------|---------------------|-----------------|
|               | Top                         |      | Bottom |      | Top                        |      | Bottom |      |                                 |                            |              |                     |                 |
|               | L                           | W    | L      | W    | L                          | W    | L      | W    |                                 |                            |              |                     |                 |
| DC 2012-07 SP | 19.6                        | 11.6 | 17.1   | 9.3  | 17.7                       | 9.9  | 16.5   | 8.7  | 7.3                             | 6.2                        | 3.1          | 0.5                 | 7,200           |
| DC 2115-09 SP | 21.9                        | 15.3 | 19.2   | 13.3 | 20.1                       | 14.3 | 18.9   | 12.0 | 9.7                             | 8.2                        | 4.7          | 1.3                 | 4,680           |
| DC 2115-09 HP | 21.9                        | 15.5 | 19.1   | 13.2 | 20.1                       | 14.4 | 19.3   | 13.3 | 9.5                             | 8.2                        | 5.2          | 1.3                 | 4,680           |
| DC 2115-12 SP | 21.9                        | 15.2 | 18.9   | 12.7 | 19.7                       | 14.0 | 18.0   | 12.2 | 12.8                            | 11.0                       | 5.4          | 1.7                 | 3,840           |
| DC 2115-12 HP | 21.9                        | 15.5 | 18.6   | 12.8 | 19.8                       | 14.1 | 18.1   | 12.4 | 12.8                            | 11.2                       | 6.1          | 1.7                 | 4,352           |
| DC 2115-17 HP | 21.9                        | 15.2 | 18.6   | 13.0 | 20.1                       | 14.3 | 18.4   | 12.8 | 17.2                            | 15.8                       | 7.7          | 2.3                 | 3,456           |
| DC 2213-12 SP | 22.3                        | 13.0 | 18.9   | 10.9 | 20.0                       | 11.3 | 18.7   | 10.1 | 13.4                            | 11.8                       | 5.2          | 1.5                 | 4,480           |
| DC 2515-14 SP | 25.3                        | 16.3 | 22.0   | 13.3 | 23.3                       | 14.5 | 21.6   | 12.8 | 13.9                            | 12.2                       | 7.2          | 2.2                 | 2,600           |
| DC 2717-12 SP | 27.3                        | 17.2 | 24.4   | 14.6 | 25.2                       | 15.5 | 23.7   | 13.9 | 12.6                            | 11.0                       | 7.7          | 2.5                 | 3,536           |
| DC 2820-15 HP | 28.1                        | 20.8 | 25.8   | 18.8 | 26.0                       | 19.0 | 25.0   | 18.0 | 15.6                            | 14.0                       | 13.2         | 3.8                 | 1,320           |



DC 2515-14, open lid



DC 2115-09

**Nestable Containers with Metal Hinge**

|                |      |      |      |      |      |      |      |      |      |      |     |     |       |
|----------------|------|------|------|------|------|------|------|------|------|------|-----|-----|-------|
| DC 1813-15 SM* | 17.4 | 12.9 | 14.4 | 10.9 | 15.2 | 11.8 | 14.0 | 10.5 | 13.6 | 13.5 | 5.8 | 1.3 | 4,416 |
| DC 1813-15 HM* | 17.4 | 12.9 | 14.4 | 10.9 | 15.2 | 11.8 | 14.0 | 10.5 | 13.6 | 13.5 | 6.1 | 1.3 | 4,416 |
| DC 2420-12 SM* | 23.8 | 19.2 | 21.4 | 17.4 | 22.3 | 18.1 | 20.5 | 16.5 | 12.5 | 11.0 | 7.7 | 2.4 | 2,880 |

**Distribution Dolly Specifications:**



Dolly 2818

|   |      |      |     |     |     |     |     |     |     |     |      |     |       |
|---|------|------|-----|-----|-----|-----|-----|-----|-----|-----|------|-----|-------|
| Dolly 2818 (for use with DC 2717-12 and comes standard with 4" casters) | 28.5 | 18.5 | N/A | N/A | N/A | N/A | N/A | N/A | 6.5 | N/A | 13.0 | N/A | 900   |
| Dolly 2818 (for use with DC 2717-12 and ships without casters)          | 28.5 | 18.5 | N/A | N/A | N/A | N/A | N/A | N/A | 6.5 | N/A | 5.0  | N/A | 1,716 |